

Reliability of a series system with redundancy and one repair facility

Yuriy V. Zhernovyi * · Soltan A. Aliyev · Yaroslav I. Yeleyko

Received: 13.03.2019 / Revised: 30.07.2020 / Accepted: 18.08.2020

Abstract. *In this paper we propose a method for studying the reliability of series systems with redundancy and one repair facility. The approach based on the use of fictitious phases and hyperexponential approximations of arbitrary distributions by method of moments. We define conditions for the variation coefficients of the gamma distributions and Weibull distributions, for which the best accuracy of calculating the steady-state probabilities is achieved in comparison with the results of simulation modeling.*

Keywords. reliability, recoverable system, redundancy, series system, hyperexponential approximation, fictitious phases, method of moments.

Mathematics Subject Classification (2010): 2010 Mathematics Subject Classification: 60G10, 60J28, 60K25, 93B40

1 Introduction

Series systems of identical independent units with a common group of redundant units are common in engineering practice. Formally, such a structure appears if a system consists of units of several types [4]. A set of units of the same type can be considered as a series system, for which there is a stock of spare units. It is reasonable to consider these spare units as unloaded; these units wait for being switched into operating position after one of operating units has failed. Failed units are directed to a repair shop, from where after recovery they again enter the systems stock. Switching of spare unit into an operating position is usually assumed instantaneous.

Recoverable series systems differ by their recovery processes. Assume that a system continues to stay in an operational state after failure, so during recovering a currently failed

* Corresponding author

Y.V. Zhernovyi
Ivan Franko National University of Lviv, Lviv, Ukraine
E-mail: yuriy.zhernovyy@lnu.edu.ua

S.A. Aliyev
Institute of Mathematics and Mechanics of NAS of Azerbaijan, AZ 1141, Baku, Azerbaijan
E-mail: soltanaliyev@yahoo.com

Y.I. Yeleyko
Ivan Franko National University of Lviv, Lviv, Ukraine
Jan Kochanowski University in Kielce, Kielce, Poland
E-mail: yikts@yahoo.com

unit new failures may appear. In principle, in this case one can observe even a situation when all system units have failed. It can happen if, for instance, a recovery process is very slow. In addition, the number of repair facilities can be restricted, so failed units can form a queue for recovering. We restrict ourselves to one repair facility.

Consider a system that consists of $r = n + m$ identical units, namely, n main operating units and m unloaded redundant units. The system stops functioning in normal mode at the moment when the number of failed units reaches $m + 1$. Assume that those $n - 1$ units that were serviceable at the moment of system failure, in idle time during recovery, continue to operate and may fail.

If we consider the described system as a single-channel queueing system, then in the absence of redundant units ($m = 0$), it is a classical closed queueing system [2]. The closed system is also known as a system with a finite number of sources or the Engset system.

In most academic approaches, a random time to failure and a random recovery time are assumed exponentially distributed for all units that gives a possibility to use the Markov model for reliability study. In this paper we consider arbitrary distributions of the units' time to failure and recovery time.

The method of potentials was used in [5] to construct an algorithm that makes it possible to calculate the steady-state distribution of the number of failed units for a single-channel closed system with an exponential distribution of the units' time to failure and an arbitrary distribution of recovery time. This method is not suitable for arbitrary distributions of the units' time to failure.

In [2] we propose a method for calculating steady-state probability distributions of the closed queueing systems with exponential distribution of the time to failure and an arbitrary distribution of recovery time. The approach based on the use of fictitious phases and hyperexponential approximations by method of moments. We consider queueing systems with the number of channels $n = 1, 2$ and 3 .

Works [1–3, 6, 7] show that the use of hyperexponential approximation (H_l) makes it possible to determine with high accuracy the steady-state probabilities of non-Markovian queueing systems. These probabilities are calculated using solutions of a system of linear algebraic equations obtained by the method of fictitious phases. To find parameters of the H_l -approximation of a certain distribution it is sufficient to solve the system of equations of the moments method. For the values $V < 1$ of the variation coefficient, roots of this system are complex-valued or paradoxical (i.e., negative or with probabilities that exceed the boundaries of the interval $[0, 1]$), but in most cases as a result of summation of probabilities of microstates, their complex-valued and paradoxical parts are annihilated.

The purpose of the paper is to use of the hyperexponential approximation method for studying the reliability of series systems with redundancy and one repair facility with arbitrary distributions of the units' time to failure and recovery time. We define conditions for the variation coefficients of the gamma distributions and Weibull distributions, for which the best accuracy of calculating the steady-state probabilities is achieved in comparison with the results of simulation modeling.

Let p_k be the steady-state probability of having k failed units, then the stationary reliability indices of the system are determined by the formulas:

$$K = \sum_{k=0}^m p_k, \quad N = \sum_{k=0}^r k p_k, \quad Q = \sum_{k=1}^{r-1} k p_{k+1}, \quad W = Q/\Lambda, \quad \Lambda = \sum_{k=0}^{r-1} \Lambda_k p_k,$$

$$\Lambda_k = \begin{cases} n/T, & 0 \leq k \leq m; \\ (r - k)/T, & m + 1 \leq k \leq r - 1. \end{cases}$$

Here K is the stationary availability coefficient, N is the average number of failed units, Q is the average queue for recovering, W is the mean waiting time for recovering and T is the mean time to failure of an unit.

2 Equations for steady-state probabilities

The hyperexponential distribution of order l is a phase-type distribution and provides for choosing one of l alternative phases by a random process. With probability y_i , the process is in the i th phase during an exponentially distributed time with a parameter θ_i .

Suppose that the units' time to failure is distributed according to the hyperexponential law H_4 with probabilities α_i and parameters λ_i ($1 \leq i \leq 4$) and the units' recovery times are independent random variables distributed according to the hyperexponential law H_l ($l \geq 2$) with probabilities β_s and parameters μ_s ($1 \leq s \leq l$). Let us denote the corresponding queueing system by $H_4/H_l/1/r$ and we will use it for approximate calculation of the steady-state probabilities of the $G/G/1/r$ queueing system. We restrict ourselves to considering the H_4 distribution, since calculations show that such an order of hyperexponential distribution provides sufficient accuracy for approximating an arbitrary distribution of the time to failure.

Let us enumerate the $H_4/H_l/1/r$ system's states as follows: $x_{0(i,j,u,v)}$ is the state, when there are 0 failed units, and i, j, u, v are the numbers of units for which the time to failure is in the first, second, third and fourth phase, respectively; $x_{k(i,j,u,v,s)}$ is the state, when there are k failed units ($1 \leq k \leq r$), and i, j, u, v are the numbers of units for which the time to failure is in the first, second, third and fourth phase, respectively, and s is the phase number of recovery time. We denote by $p_{0(i,j,u,v)}$ and $p_{k(i,j,u,v,s)}$, steady-state probabilities that the system is in the each of these states respectively. Since the process of changing the states of the system is Markovian with continuous time, for the steady-state probabilities $p_{0(i,j,u,v)}$ and $p_{k(i,j,u,v,s)}$ we obtain a system of linear algebraic equations that follows from the Kolmogorov system of differential equations.

Let us write the equations corresponding to the states $x_{0(n,0,0,0)}$, $x_{0(0,n,0,0)}$, $x_{0(0,0,n,0)}$ and $x_{0(0,0,0,n)}$:

$$\begin{aligned} -n\lambda_1 p_{0(n,0,0,0)} + \sum_{i=1}^l \mu_i p_{1(n,0,0,0,i)} &= 0, & -n\lambda_2 p_{0(0,n,0,0)} + \sum_{i=1}^l \mu_i p_{1(0,n,0,0,i)} &= 0, \\ -n\lambda_3 p_{0(0,0,n,0)} + \sum_{i=1}^l \mu_i p_{1(0,0,n,0,i)} &= 0, & -n\lambda_4 p_{0(0,0,0,n)} + \sum_{i=1}^l \mu_i p_{1(0,0,0,n,i)} &= 0. \end{aligned}$$

On the example of the equation corresponding to the state $x_{0(i,n-i,0,0)}$, we show what is the structure of the equations for the states $x_{0(i,0,n-i,0)}$, $x_{0(i,0,0,n-i)}$, $x_{0(0,i,n-i,0)}$, $x_{0(0,i,0,n-i)}$ and $x_{0(0,0,i,n-i)}$:

$$-(i\lambda_1 + (n-i)\lambda_2) p_{0(i,n-i,0,0)} + \sum_{j=1}^l \mu_j p_{1(i,n-i,0,0,j)} = 0, \quad 1 \leq i \leq n-1.$$

Let us write the equation corresponding to the state $x_{0(i,j,n-i-j,0)}$:

$$\begin{aligned} -(i\lambda_1 + j\lambda_2 + (n-i-j)\lambda_3) p_{0(i,j,n-i-j,0)} + \sum_{s=1}^l \mu_s p_{1(i,j,n-i-j,0,s)} &= 0, \\ 1 \leq i \leq n-2, \quad 1 \leq j \leq n-1-i. \end{aligned} \quad (2.1)$$

The equations for the states $x_{0(i,j,0,n-i-j)}$, $x_{0(i,0,j,n-i-j)}$ and $x_{0(0,i,j,n-i-j)}$ have a similar structure with (2.1).

Let us write the equation corresponding to the state $x_{0(i,j,s,n-i-j-s)}$:

$$-(i\lambda_1 + j\lambda_2 + s\lambda_3 + (n-i-j-s)\lambda_4)p_{0(i,j,s,n-i-j-s)} + \sum_{u=1}^l \mu_u p_{1(i,j,s,n-i-j-s,u)} = 0,$$

$$1 \leq i \leq n-3, \quad 1 \leq j \leq n-2-i, \quad 1 \leq s \leq n-1-i-j.$$

Let us give examples of equations corresponding to the states $x_{1(n,0,0,0,i)}$, $x_{1(0,n,0,0,i)}$, $x_{1(0,0,n,0,i)}$, $x_{1(0,0,0,n,i)}$, $x_{1(i,n-i,0,0,j)}$, $x_{1(i,0,n-i,0,j)}$, $x_{1(i,0,0,n-i,j)}$, $x_{1(0,i,n-i,0,j)}$, $x_{1(0,i,0,n-i,j)}$, $x_{1(0,0,i,n-i,j)}$, $x_{1(i,j,n-i-j,0,s)}$, $x_{1(i,j,0,n-i-j,s)}$, $x_{1(i,0,j,n-i-j,s)}$, $x_{1(0,i,j,n-i-j,s)}$ and $x_{1(i,j,s,n-i-j-s,v)}$:

$$-(n\lambda_1 + \mu_i)p_{1(n,0,0,0,i)} + \beta_i \sum_{j=1}^l \mu_j p_{2(n,0,0,0,j)} + \alpha_1 \beta_i (n\lambda_1 p_{0(n,0,0,0)})$$

$$+ \lambda_2 p_{0(n-1,1,0,0)} + \lambda_3 p_{0(n-1,0,1,0)} + \lambda_4 p_{0(n-1,0,0,1)} = 0, \quad 1 \leq i \leq l;$$

$$-(i\lambda_1 + (n-i)\lambda_2 + \mu_j)p_{1(i,n-i,0,0,j)} + \beta_j \sum_{s=1}^l \mu_s p_{2(i,n-i,0,0,s)} + \alpha_1 \beta_j (i\lambda_1 p_{0(i,n-i,0,0)})$$

$$+ (n+1-i)\lambda_2 p_{0(i-1,n+1-i,0,0)} + \lambda_3 p_{0(i-1,n-i,1,0)} + \lambda_4 p_{0(i-1,n-i,0,1)}$$

$$+ \alpha_2 \beta_j ((i+1)\lambda_1 p_{0(i+1,n-1-i,0,0)})$$

$$+ (n-i)\lambda_2 p_{0(i,n-i,0,0)} + \lambda_3 p_{0(i,n-1-i,1,0)} + \lambda_4 p_{0(i,n-1-i,0,1)} = 0,$$

$$1 \leq i \leq n-1, \quad 1 \leq j \leq l;$$

$$-(i\lambda_1 + j\lambda_2 + (n-i-j)\lambda_3 + \mu_s)p_{1(i,j,n-i-j,0,s)} + \beta_s \sum_{u=1}^l \mu_u p_{2(i,j,n-i-j,0,u)}$$

$$+ \alpha_1 \beta_s (i\lambda_1 p_{0(i,j,n-i-j,0)} + (j+1)\lambda_2 p_{0(i-1,j+1,n-i-j,0)})$$

$$+ (n+1-i-j)\lambda_3 p_{0(i-1,j,n+1-i-j,0)} + \lambda_4 p_{0(i-1,j,n-i-j,1)}$$

$$+ \alpha_2 \beta_s ((i+1)\lambda_1 p_{0(i+1,j-1,n-i-j,0)} + j\lambda_2 p_{0(i,j,n-i-j,0)})$$

$$+ (n+1-i-j)\lambda_3 p_{0(i,j-1,n+1-i-j,0)} + \lambda_4 p_{0(i,j-1,n-i-j,1)}$$

$$+ \alpha_3 \beta_s ((i+1)\lambda_1 p_{0(i+1,j,n-1-i-j,0)} + (j+1)\lambda_2 p_{0(i,j+1,n-1-i-j,0)})$$

$$+ (n-i-j)\lambda_3 p_{0(i,j,n-i-j,0)} + \lambda_4 p_{0(i,j,n-1-i-j,1)} = 0,$$

$$1 \leq i \leq n-2, \quad 1 \leq j \leq n-1-i, \quad 1 \leq s \leq l;$$

$$-(i\lambda_1 + j\lambda_2 + s\lambda_3 + (n-i-j-s)\lambda_4 + \mu_u)p_{1(i,j,s,n-i-j-s,u)}$$

$$+ \beta_u \sum_{v=1}^l \mu_v p_{2(i,j,s,n-i-j-s,v)}$$

$$+ \beta_u \alpha_1 (i\lambda_1 p_{0(i,j,s,n-i-j-s)} + (j+1)\lambda_2 p_{0(i-1,j+1,s,n-i-j-s)})$$

$$+ (s+1)\lambda_3 p_{0(i-1,j,s+1,n-i-j-s)} (n+1-i-j-s)\lambda_4 p_{0(i-1,j,s,n+1-i-j-s)}$$

$$+ \beta_u \alpha_2 ((i+1)\lambda_1 p_{0(i+1,j-1,s,n-i-j-s)} + j\lambda_2 p_{0(i,j,s,n-i-j-s)})$$

$$+ (s+1)\lambda_3 p_{0(i,j-1,s+1,n-i-j-s)} + (n+1-i-j-s)\lambda_4 p_{0(i,j-1,s,n+1-i-j-s)}$$

$$+ \beta_u \alpha_3 ((i+1)\lambda_1 p_{0(i+1,j,s-1,n-i-j-s)} + (j+1)\lambda_2 p_{0(i,j+1,s-1,n-i-j-s)})$$

$$\begin{aligned}
& + s\lambda_3 p_0(i,j,s,n-i-j-s) + (n+1-i-j-s)\lambda_4 p_0(i,j,s-1,n+1-i-j-s) \\
& + \beta_u \alpha_4 ((i+1)\lambda_1 p_0(i+1,j,s,n-1-i-j-s) + (j+1)\lambda_2 p_0(i,j+1,s,n-1-i-j-s) \\
& + (s+1)\lambda_3 p_0(i,j,s+1,n-1-i-j-s) + (n-i-j-s)\lambda_4 p_0(i,j,s,n-i-j-s)) = 0, \\
& 1 \leq i \leq n-3, \quad 1 \leq j \leq n-2-i, \quad 1 \leq s \leq n-1-i-j, \quad 1 \leq u \leq l.
\end{aligned}$$

The structure of equations corresponding to the states $x_{k(n,0,0,0,i)}$, $x_{k(0,n,0,0,i)}$, $x_{k(0,0,n,0,i)}$, $x_{k(0,0,0,n,i)}$, $x_{k(i,n-i,0,0,j)}$, $x_{k(i,0,n-i,0,j)}$, $x_{k(i,0,0,n-i,j)}$, $x_{k(0,i,n-i,0,j)}$, $x_{k(0,i,0,n-i,j)}$, $x_{k(0,0,i,n-i,j)}$, $x_{k(i,j,n-i-j,0,s)}$, $x_{k(i,j,0,n-i-j,s)}$, $x_{k(i,0,j,n-i-j,s)}$, $x_{k(0,i,j,n-i-j,s)}$ and $x_{k(i,j,s,n-i-j-s,v)}$ for $k \in \{2, 3, \dots, m-1\}$ differs from the structure of equations (2.2) only in the absence of the multiplier β_i before the probabilities $p_{k-1}(\dots, \dots, i)$:

$$\begin{aligned}
& - (n\lambda_1 + \mu_i) p_{k(n,0,0,0,i)} + \beta_i \sum_{j=1}^l \mu_j p_{k+1}(n,0,0,0,j) + \alpha_1 (n\lambda_1 p_{k-1}(n,0,0,0,i) \\
& + \lambda_2 p_{k-1}(n-1,1,0,0,i) + \lambda_3 p_{k-1}(n-1,0,1,0,i) + \lambda_4 p_{k-1}(n-1,0,0,1,i)) = 0, \\
& 2 \leq k \leq m-1, \quad 1 \leq i \leq l; \\
& - (i\lambda_1 + (n-i)\lambda_2 + \mu_j) p_{k(i,n-i,0,0,j)} + \beta_j \sum_{s=1}^l \mu_s p_{k+1}(i,n-i,0,0,s) \\
& + \alpha_1 (i\lambda_1 p_{k-1}(i,n-i,0,0,j) + (n+1-i)\lambda_2 p_{k-1}(i-1,n+1-i,0,0,j) + \lambda_3 p_{k-1}(i-1,n-i,1,0,j) \\
& + \lambda_4 p_{k-1}(i-1,n-i,0,1,j)) \\
& + \alpha_2 ((i+1)\lambda_1 p_{k-1}(i+1,n-1-i,0,0,j) + (n-i)\lambda_2 p_{k-1}(i,n-i,0,0,j) + \lambda_3 p_{k-1}(i,n-1-i,1,0,j) \\
& + \lambda_4 p_{k-1}(i,n-1-i,0,1,j)) = 0, \quad 2 \leq k \leq m-1, \quad 1 \leq i \leq n-1, \quad 1 \leq j \leq l; \quad \dots
\end{aligned}$$

Let us give examples of equations corresponding to the states $x_{k(r-k,0,0,0,i)}$, $x_{k(0,r-k,0,0,i)}$, $x_{k(0,0,r-k,0,i)}$, $x_{k(0,0,0,r-k,i)}$, $x_{k(i,r-k-i,0,0,j)}$, $x_{k(i,0,r-k-i,0,j)}$, $x_{k(i,0,0,r-k-i,j)}$, $x_{k(0,i,r-k-i,0,j)}$, $x_{k(0,0,i,r-k-i,j)}$, $x_{k(i,j,r-k-i-j,0,s)}$, $x_{k(i,j,0,r-k-i-j,s)}$, $x_{k(i,0,j,r-k-i-j,s)}$ and $x_{k(0,i,j,r-k-i-j,s,v)}$ for $k \in \{m+1, m+2, \dots, r-1\}$

$$\begin{aligned}
& - ((r-k)\lambda_1 + \mu_i) p_{k(r-k,0,0,0,i)} + \alpha_1 \beta_i \sum_{j=1}^l \mu_j p_{k+1}(r-k-1,0,0,0,j) \\
& + (r-k+1)\lambda_1 p_{k-1}(r-k+1,0,0,0,i) + \lambda_2 p_{k-1}(r-k,1,0,0,i) + \lambda_3 p_{k-1}(r-k,0,1,0,i) \\
& + \lambda_4 p_{k-1}(r-k,0,0,1,i) = 0, \quad m+1 \leq k \leq r-1, \quad 1 \leq i \leq l; \\
& - (i\lambda_1 + (r-k-i)\lambda_2 + \mu_j) p_{k(i,r-k-i,0,0,j)} + \beta_j \sum_{s=1}^l \mu_s (\alpha_1 p_{k+1}(i-1,r-k-i,0,0,s) \\
& + \alpha_2 p_{k+1}(i,r-k-i-1,0,0,s)) + (i+1)\lambda_1 p_{k-1}(i+1,r-k-i,0,0,j) \\
& + (r-k-i+1)\lambda_2 p_{k-1}(i,r-k-i+1,0,0,j) + \lambda_3 p_{k-1}(i,r-k-i,1,0,j) \\
& + \lambda_4 p_{k-1}(i,r-k-i,0,1,j) = 0, \quad m+1 \leq k \leq r-2, \quad 1 \leq i \leq r-k-1, \quad 1 \leq j \leq l; \\
& - (i\lambda_1 + j\lambda_2 + (r-k-i-j)\lambda_3 + \mu_s) p_{k(i,j,r-k-i-j,0,s)} \\
& + \beta_s \sum_{u=1}^l \mu_u (\alpha_1 p_{k+1}(i-1,j,r-k-i-j,0,u) + \alpha_2 p_{k+1}(i,j-1,r-k-i-j,0,u) \\
& + \alpha_3 p_{k+1}(i,j,r-k-i-j-1,0,u)) + (i+1)\lambda_1 p_{k-1}(i+1,j,r-k-i-j,0,s)
\end{aligned}$$

$$\begin{aligned}
& + (j+1)\lambda_2 p_{k-1}(i, j+1, r-k-i-j, 0, s) + (r-k-i-j+1)\lambda_3 p_{k-1}(i, j, r-k-i-j+1, 0, s) \\
& + \lambda_4 p_{k-1}(i, j, r-k-i-j, 1, s) = 0, \\
& m+1 \leq k \leq r-3, \quad 1 \leq i \leq r-k-2, \quad 1 \leq j \leq r-k-i-1, \quad 1 \leq s \leq l; \\
& - (i\lambda_1 + j\lambda_2 + s\lambda_3 + (r-k-i-j-s)\lambda_4 + \mu_u) p_k(i, j, s, r-k-i-j-s, u) \\
& + \beta_u \sum_{v=1}^l \mu_v (\alpha_1 p_{k+1}(i-1, j, s, r-k-i-j-s, v) + \alpha_2 p_{k+1}(i, j-1, s, r-k-i-j-s, v) \\
& + \alpha_3 p_{k+1}(i, j, s-1, r-k-i-j-s, v) + \alpha_4 p_{k+1}(i, j, s, r-k-i-j-s-1, v)) \\
& + (i+1)\lambda_1 p_{k-1}(i+1, j, s, r-k-i-j-s, u) + (j+1)\lambda_2 p_{k-1}(i, j+1, s, r-k-i-j-s, u) \\
& + (s+1)\lambda_3 p_{k-1}(i, j, s+1, r-k-i-j-s, u) \\
& + (r-k-i-j-s+1)\lambda_4 p_{k-1}(i, j, s, r-k-i-j-s+1, u) = 0, \\
& m+1 \leq k \leq r-4, \quad 1 \leq i \leq r-k-3, \quad 1 \leq j \leq r-k-i-2, \\
& \quad \quad \quad 1 \leq s \leq r-k-i-j-1, \quad 1 \leq u \leq l.
\end{aligned}$$

Let us write the equation corresponding to the state $x_{r(0,0,0,0,i)}$:

$$\begin{aligned}
& -\mu_i p_{r(0,0,0,0,i)} + \lambda_1 p_{r-1(1,0,0,0,i)} + \lambda_2 p_{r-1(0,1,0,0,i)} + \lambda_3 p_{r-1(0,0,1,0,i)} \\
& + \lambda_4 p_{r-1(0,0,0,1,i)} = 0, \quad 1 \leq i \leq l.
\end{aligned}$$

The normalization condition closes the system of equations for steady-state probabilities:

$$\begin{aligned}
& \sum_{i=0}^n \sum_{j=0}^{n-i} \sum_{s=0}^{n-i-j} p_0(i, j, s, n-i-j-s) + \sum_{k=1}^m \sum_{i=0}^n \sum_{j=0}^{n-i} \sum_{s=0}^{n-i-j} \sum_{u=1}^l p_k(i, j, s, n-i-j-s, u) \\
& + \sum_{k=m+1}^r \sum_{i=0}^{r-k} \sum_{j=0}^{r-k-i} \sum_{s=0}^{r-k-i-j} \sum_{u=1}^l p_k(i, j, s, r-k-i-j-s, u) = 1.
\end{aligned}$$

Solving the system obtained by the method of fictitious phases, we find the steady-state probabilities p_k of having k failed units, using the formulas

$$\begin{aligned}
p_0 &= \sum_{i=0}^n \sum_{j=0}^{n-i} \sum_{s=0}^{n-i-j} p_0(i, j, s, n-i-j-s), \\
p_k &= \sum_{i=0}^n \sum_{j=0}^{n-i} \sum_{s=0}^{n-i-j} \sum_{u=1}^l p_k(i, j, s, n-i-j-s, u), \quad 1 \leq k \leq m; \\
p_k &= \sum_{i=0}^{r-k} \sum_{j=0}^{r-k-i} \sum_{s=0}^{r-k-i-j} \sum_{u=1}^l p_k(i, j, s, r-k-i-j-s, u), \quad m+1 \leq k \leq r.
\end{aligned}$$

3 Numerical results

Let $\Gamma(V)$, $W(V)$ and $U[a, b]$ denote the gamma distribution, Weibull distribution with coefficients of variation V , and uniform distribution on the interval $[a, b]$, respectively.

Table 1 List of distributions D_1 and D_2 for which condition $\Delta_{(6,5)} < 10^{-4}$ holds

D_1	D_2	Values of V_2	D_1	D_2	Values of V_1
$\Gamma(0.001)$	$\Gamma(V_2)$	[0.7, 1.5]	$\Gamma(V_1)$	$\Gamma(0.001)$	0.4, 0.51, [0.7, 100]
$\Gamma(0.001)$	$W(V_2)$	[0.8, 1.2]	$W(V_1)$	$\Gamma(0.001)$	[0.4, 10]
$\Gamma(0.4)$	$\Gamma(V_2)$	[0.001, 0.3], [0.51, 1.6]	$\Gamma(V_1)$	$\Gamma(0.4)$	0.3, [0.8, 100]
$\Gamma(0.4)$	$W(V_2)$	[0.001, 1.3]	$W(V_1)$	$\Gamma(0.4)$	[0.3, 10]
$W(0.4)$	$\Gamma(V_2)$	[0.001, 1.6]	$W(V_1)$	$W(0.4)$	[0.3, 10]
$W(0.4)$	$W(V_2)$	[0.001, 1.3]	$\Gamma(V_1)$	$W(0.4)$	[0.3, 100]
$U[0, 8]$	$\Gamma(V_2)$	[0.001, 1.4]	$\Gamma(V_1)$	$U[0, 2]$	[0.3, 100]
$U[0, 8]$	$W(V_2)$	[0.001, 1.3]	$W(V_1)$	$U[0, 2]$	[0.3, 10]
$\Gamma(0.8)$	$\Gamma(V_2)$	[0.001, 1.8]	$\Gamma(V_1)$	$\Gamma(0.8)$	[0.001, 100]
$\Gamma(0.8)$	$W(V_2)$	[0.001, 1.4]	$W(V_1)$	$\Gamma(0.8)$	[0.001, 10]
$W(0.8)$	$\Gamma(V_2)$	[0.001, 1.8]	$\Gamma(V_1)$	$W(0.8)$	[0.001, 100]
$W(0.8)$	$W(V_2)$	[0.001, 1.4]	$W(V_1)$	$W(0.8)$	[0.001, 10]
$\Gamma(1.3)$	$\Gamma(V_2)$	[0.001, 1.6]	$\Gamma(V_1)$	$\Gamma(1.3)$	[0.001, 100]
$\Gamma(1.3)$	$W(V_2)$	[0.001, 1.4]	$W(V_1)$	$\Gamma(1.3)$	[0.001, 10]
$W(1.3)$	$\Gamma(V_2)$	[0.001, 1.7]	$\Gamma(V_1)$	$W(1.3)$	[0.4, 100]
$W(1.3)$	$W(V_2)$	[0.001, 1.4]	$W(V_1)$	$W(1.3)$	[0.4, 10]
$\Gamma(100)$	$\Gamma(V_2)$	[0.001, 1.5]	$\Gamma(V_1)$	$\Gamma(2)$	–
$\Gamma(100)$	$W(V_2)$	[0.001, 1.3]	$W(V_1)$	$\Gamma(2)$	–
$W(10)$	$\Gamma(V_2)$	[0.001, 1.8]	$\Gamma(V_1)$	$W(2)$	–
$W(10)$	$W(V_2)$	[0.001, 1.4]	$W(V_1)$	$W(2)$	–

In this section we present the results of using the $H_4/H_5/1/r$ and $H_4/H_6/1/r$ systems to calculate the probabilities p_k for the $G/G/1/r$ series recoverable system with redundancy. We consider the gamma distributions, Weibull distributions and uniform distributions of units' time to failure (named distribution D_1) and units' recovery time (named distribution D_2).

For the $M/G/1/r$ queueing systems the deviation $\Delta_{sim} = \sum_{k=0}^r |p_k - p_{k(sim)}|$ of distribution $\{p_{k(sim)}\}$, obtained using the GPSS World simulation system [8], from the distribution $\{p_k\}$, obtained using the method of potentials, exceeds 10^{-4} [7]. This statement is confirmed if we calculate Δ_{sim} for the considered series system with exponential distributions of the units' time to failure and recovery time. The GPSS World simulation model of the series recoverable system with redundancy is constructed in [9].

We determine the values of the variation coefficients of the $\Gamma(V)$ and $W(V)$ distributions, for which the condition $\Delta_{(6,5)} < 10^{-4}$ holds. If this condition is fulfilled, the distribution $\{p_{k(6)}\}$ is a more accurate approximation to the true steady-state distribution $\{p_k\}$, than the distribution obtained using the GPSS World simulation system. Here $\Delta_{(6,5)} = \sum_{k=0}^r |p_{k(6)} - p_{k(5)}|$ gives an opportunity to estimate the deviation of distributions $\{p_{k(6)}\}$ from distributions $\{p_{k(5)}\}$, where $p_{k(l)}$ are values of probabilities p_k obtained using the $H_4/H_l/1/r$ system as an approximation of the $G/G/1/r$ system.

Let us take $n = 4$, $m = 3$, $T = 4$ and $\tau = 1$, where τ is the mean units' recovery time. Thus, the average values of the distributions D_1 and D_2 are equal to 4 and 1 respectively.

The numerical results are presented in Table 1. Of all the intervals corresponding to the $\Gamma(V)$ distributions, the values $V = 0.5$ and $V = 1/\sqrt{2}$ of the variation coefficient should be excluded, since for the $\Gamma(0.5)$ distribution it is not possible to construct approximations with the help of hyperexponential distributions of order higher than the third, and hyperexponential approximations do not exist for the $\Gamma(1/\sqrt{2})$ distribution.

The data in Table 1 show that a high accuracy of approximation is achieved for a wider range of values of the variation coefficient of the distribution D_1 compared to the distribution D_2 . Namely, for the distribution D_1 , the maximum interval for the variation coefficient

Table 2 Results of the calculation of steady-state reliability indices for different distributions D_1 and D_2

D_1	D_2	N	K	W	$\Delta_{(6,5)}$
$\Gamma(0.001)$	$W(0.6)$	2.419	0.798	1.583	$2.30 \cdot 10^{-6}$
$\Gamma(0.001)$	$\Gamma(0.7)$	2.436	0.776	1.641	$3.56 \cdot 10^{-8}$
$\Gamma(0.001)$	$W(0.8)$	2.484	0.748	1.737	$2.70 \cdot 10^{-6}$
$\Gamma(0.001)$	$\Gamma(1.3)$	2.654	0.670	2.169	$3.67 \cdot 10^{-5}$
$\Gamma(0.001)$	$\Gamma(1.5)$	2.720	0.649	2.347	$8.90 \cdot 10^{-5}$
$W(0.4)$	$\Gamma(0.001)$	2.305	0.868	1.396	$2.41 \cdot 10^{-6}$
$W(0.5)$	$\Gamma(0.001)$	2.347	0.834	1.472	$3.54 \cdot 10^{-7}$
$\Gamma(0.7)$	$\Gamma(0.001)$	2.425	0.778	1.617	$2.86 \cdot 10^{-6}$
$\Gamma(0.8)$	$\Gamma(0.001)$	2.461	0.753	1.690	$4.69 \cdot 10^{-7}$
$\Gamma(1.5)$	$\Gamma(0.001)$	2.696	0.628	2.177	$9.18 \cdot 10^{-6}$
$W(10)$	$\Gamma(0.001)$	2.659	0.645	2.100	$3.88 \cdot 10^{-8}$
$\Gamma(100)$	$\Gamma(0.001)$	3.284	0.363	3.599	$9.28 \cdot 10^{-6}$
$\Gamma(0.4)$	$\Gamma(0.1)$	2.321	0.864	1.415	$2.26 \cdot 10^{-6}$
$\Gamma(0.4)$	$\Gamma(0.3)$	2.356	0.834	1.480	$6.06 \cdot 10^{-7}$
$\Gamma(0.4)$	$W(0.4)$	2.391	0.811	1.542	$8.54 \cdot 10^{-7}$
$\Gamma(0.4)$	$W(1.3)$	2.652	0.667	2.177	$7.70 \cdot 10^{-5}$
$\Gamma(0.4)$	$\Gamma(1.6)$	2.755	0.634	2.450	$7.10 \cdot 10^{-5}$
$\Gamma(0.3)$	$\Gamma(0.4)$	2.359	0.833	1.484	$2.30 \cdot 10^{-5}$
$W(0.3)$	$\Gamma(0.4)$	2.356	0.833	1.482	$2.13 \cdot 10^{-6}$
$\Gamma(0.8)$	$\Gamma(0.4)$	2.498	0.731	1.770	$4.40 \cdot 10^{-7}$
$W(10)$	$\Gamma(0.4)$	2.672	0.640	2.140	$8.02 \cdot 10^{-7}$
$\Gamma(100)$	$\Gamma(0.4)$	3.281	0.364	3.595	$4.06 \cdot 10^{-5}$
$W(0.4)$	$W(0.1)$	2.312	0.864	1.407	$2.12 \cdot 10^{-6}$
$W(0.4)$	$\Gamma(0.49)$	2.408	0.792	1.586	$4.02 \cdot 10^{-5}$
$W(0.4)$	$W(1.3)$	2.655	0.665	2.181	$7.12 \cdot 10^{-5}$
$W(0.4)$	$\Gamma(1.6)$	2.757	0.632	2.454	$6.88 \cdot 10^{-5}$
$\Gamma(0.3)$	$W(0.4)$	2.371	0.831	1.497	$3.18 \cdot 10^{-6}$
$W(0.3)$	$W(0.4)$	2.368	0.831	1.495	$2.85 \cdot 10^{-6}$
$\Gamma(0.6)$	$W(0.4)$	2.442	0.769	1.650	$3.28 \cdot 10^{-6}$
$W(10)$	$W(0.4)$	2.674	0.639	2.142	$3.69 \cdot 10^{-8}$
$\Gamma(100)$	$W(0.4)$	3.281	0.364	3.595	$3.11 \cdot 10^{-6}$
$U[0, 8]$	$W(0.1)$	2.376	0.801	1.542	$1.08 \cdot 10^{-6}$
$U[0, 8]$	$U[0, 2]$	2.511	0.731	1.782	$6.37 \cdot 10^{-6}$
$U[0, 8]$	$W(0.9)$	2.588	0.687	1.978	$1.64 \cdot 10^{-7}$
$U[0, 8]$	$\Gamma(1.4)$	2.729	0.633	2.350	$1.19 \cdot 10^{-5}$
$\Gamma(0.3)$	$U[0, 2]$	2.463	0.775	1.655	$2.83 \cdot 10^{-5}$
$W(0.4)$	$U[0, 2]$	2.474	0.763	1.688	$7.91 \cdot 10^{-6}$
$W(10)$	$U[0, 2]$	2.697	0.631	2.199	$5.50 \cdot 10^{-7}$
$\Gamma(100)$	$U[0, 2]$	3.273	0.366	3.584	$2.97 \cdot 10^{-5}$
$\Gamma(0.8)$	$W(1.3)$	2.702	0.640	2.287	$3.23 \cdot 10^{-5}$
$\Gamma(0.8)$	$\Gamma(1.4)$	2.740	0.628	2.381	$9.93 \cdot 10^{-6}$
$\Gamma(0.8)$	$W(1.4)$	2.722	0.634	2.347	$9.67 \cdot 10^{-5}$
$\Gamma(0.8)$	$\Gamma(1.8)$	2.834	0.602	2.666	$7.99 \cdot 10^{-5}$
$\Gamma(0.6)$	$\Gamma(0.8)$	2.543	0.709	1.880	$1.11 \cdot 10^{-6}$
$\Gamma(1.5)$	$\Gamma(0.8)$	2.757	0.603	2.344	$2.27 \cdot 10^{-7}$
$W(10)$	$\Gamma(0.8)$	2.714	0.625	2.259	$3.72 \cdot 10^{-7}$
$\Gamma(100)$	$\Gamma(0.8)$	3.271	0.367	3.582	$3.80 \cdot 10^{-7}$
$W(0.8)$	$W(1.4)$	2.726	0.632	2.355	$9.58 \cdot 10^{-5}$
$W(0.8)$	$\Gamma(1.8)$	2.837	0.600	2.671	$7.56 \cdot 10^{-5}$
$\Gamma(0.6)$	$W(0.8)$	2.549	0.706	1.888	$3.59 \cdot 10^{-6}$
$W(10)$	$W(0.8)$	2.716	0.624	2.263	$3.66 \cdot 10^{-8}$
$\Gamma(100)$	$W(0.8)$	3.270	0.367	3.580	$1.33 \cdot 10^{-6}$
$\Gamma(2)$	$\Gamma(0.49)$	2.843	0.562	2.512	$4.45 \cdot 10^{-8}$
$\Gamma(2)$	$\Gamma(1.5)$	2.935	0.532	2.824	$8.36 \cdot 10^{-5}$
$W(2)$	$\Gamma(0.49)$	2.769	0.600	2.346	$4.78 \cdot 10^{-8}$
$W(2)$	$\Gamma(1.5)$	2.880	0.562	2.706	$3.27 \cdot 10^{-5}$

is $[0.001, 100]$ for the gamma distributions, and it is $[0.001, 10]$ for the Weibull distributions. For the distribution D_2 , the maximum interval for the variation coefficient is $[0.001, 1.8]$ for the gamma distributions, and it is $[0.001, 1.4]$ for the Weibull distributions.

The results of calculation of reliability steady-state indices for different distributions D_1 and D_2 are given in Table 2. The presented results show that an increase in the variation coefficient of distributions D_1 and D_2 leads to an increase in the average number of failed units N and the mean waiting time for recovering W and to a decrease in the stationary availability coefficient of the system K .

4 Conclusions

This paper shows that the application of hyperexponential approximations of distributions of the units' time to failure and recovery time allow us to calculate steady-state probabilities of the series recoverable system with redundancy and one repair facility. We find these probabilities using solutions of a system of linear algebraic equations obtained by the method of fictitious phases. To obtain parameters of H_l -approximation of a certain distribution, it is necessary to solve the system of equations of the moments method. Computing the deviations $\Delta_{(6,5)}$ allows us to track the accuracy of approaching distributions $\{p_{k(t)}\}$ to the true distribution $\{p_k\}$ without the need of using simulation models. We defined conditions for the variation coefficients of the gamma distributions and Weibull distributions, for which the best accuracy of calculating the steady-state probabilities is achieved compared with the case of using simulation models.

References

1. Aliyev, S. A., Yeleyko, Y. I., Zhernovyi, Yu. V.: *Calculating steady-state probabilities of the G/M/n/m queueing systems*, Trans. Natl. Acad. Sci. Azerb. Ser. Phys.-Tech. Math. Sci., Mathematics, **39** (4), 9–16 (2019).
2. Aliyev, S. A., Yeleyko, Y. I., Zhernovyi, Yu. V.: *Calculating steady-state probabilities of closed queueing systems using hyperexponential approximation*, Caspian Journal of Applied Mathematics, Economics and Ecology, **7** (1), 46–55 (2019).
3. Ryzhikov, Yu. I., Ulanov, A. V.: *Application of hyperexponential approximation in the problems of calculating non-Markovian queueing systems*, Vestnik of Tomsk State Univ. Management, Comp. Eng. and Inform. **36** (3), 60–65 (2016) (in Russian).
4. Ushakov, I.: Probabilistic Reliability Models, *John Wiley & Sons, Hoboken* (2012).
5. Zhernovyi, Yu. V., Zhernovyi, K. Yu.: *Method of potentials for a closed system with queue length dependent service times*, Journal of Communications Technology and Electronics, **60** (12), 1341–1347 (2015).
6. Zhernovyi, Yu. V.: *Recurrence relations for two-channel systems with Erlangian service time*, Cybernetics and Systems Analysis, **54** (5), 476–483 (2018).
7. Zhernovyi, Yu.: *Computing non-Markovian Queues Using Hyperexponential Distributions*, LAP Lambert Academic Publishing, Riga (2019).
8. Zhernovyi, Yu.: *Creating Models of Queueing Systems Using GPSS World*, LAP Lambert Academic Publishing, Saarbrücken (2015).
9. Zhernovyi, Yu. V.: *Simulation Models of Reliability*, PC "Zhytomyr-Polygraph", Zhytomyr (2020) (in Ukrainian).